

(Chlorinated Polyvinyl Chloride (CPVC) Pipe and Fittings) Support Devices for Thermoplastic Sprinkler Piping

Guide Information

ITW BUILDEX

1349 W BRYN MAWR AVE
ITASCA, IL 60143 USA

EX6140

CPVC pipe hangers, Model GST-10, self-threading anchor for supporting 3/4, 1, 1-1/4 and 1-1/2 in. CPVC pipe only when attached vertically to a structured wood timber or joist of minimum 1-1/2 in. thickness or plywood of 3/4 in. minimum thickness; Model SWG-10 self-threading anchor for supporting 3/4, 1, 1-1/4 and 1-1/2, CPVC pipe only when attached directly to the side of a structural wood joist of 1-1/2 in. minimum thickness.

[Page Top](#)

[UL Listed and Classified Products](#)

[Notice of Disclaimer](#)

[UL Recognized Components](#)

[Questions?](#)

[Products Certified for Canada](#)

This page and all contents are Copyright © 2004 by Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2004 Underwriters Laboratories Inc.®"